

# **X25API Programming Manual**

**Author: Nenad Corbic**











```
memset(&api_data,0,sizeof(x25api_t));
sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
api_data.hdr.length = strlen(api_data.data);
```

```
int connect(sock, NULL, NULL);
```

```
int connect(sock, NULL, NULL);
```

```
SIOC_WANPIPE_SET_CALL_DATA :
```

  

```
SIOC_WANPIPE_GET_CALL_DATA:
```

```
SIOC_WANPIPE_ACCEPT_CALL:
```

```
SIOC_WANPIPE_CLEAR_CALL:
```

```
SIOC_WANPIPE_RESET:
```

```
  memset(&api_data,0,sizeof(x25api_t));
  sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
  api_data.hdr.length = strlen(api_data.data);
```

```
  memset(&api_data,0,sizeof(x25api_t));
  sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
  api_data.hdr.length = strlen(api_data.data);
```

```
  memset(&api_data,0,sizeof(x25api_t));
  sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
  api_data.hdr.length = strlen(api_data.data);
```

```
  memset(&api_data,0,sizeof(x25api_t));
  sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
  api_data.hdr.length = strlen(api_data.data);
```

```
  memset(&api_data,0,sizeof(x25api_t));
  sprintf(api_data.data, "-d1234 -s2345 -f3232 -uC21010");
  api_data.hdr.length = strlen(api_data.data);
```





uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t data;

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/

flags

uint8\_t data;

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/  
uint8\_t \*data; /\* pointer to the data to be sent \*/

flags

uint8\_t \*data; /\* pointer to the data to be sent \*/

**Note:** uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t \*data; /\* pointer to the data to be sent \*/

uint8\_t data;



server.c and client.c

C

server.c and client.c

C

server.c and client.c

C

server.c and client.c